

Product Data

Castrol Iloform PN 226

Neat forming oil

Description

Castrol Iloform™ PN 226 is a medium viscosity, chlorinated and sulphurised, forming oil. It is specifically developed for medium to heavy duty deep drawing operations. It is a blend of high performance extreme pressure and boundary lubricants and anti wear additives, in a fully solvent refined paraffinic mineral oil.

Application

Iloform PN 226 is specially formulated for use in single die and progressive die presses for medium to heavy deep drawing applications. It is suitable for use on steels, stainless steels and nickel alloy steels

Advantages

- Formulated on solvent refined mineral oil. Does not contain hazardous aromatic constituents.
- Contains high performance extreme pressure, lubricity and anti wear additives. Maximises die life and provides excellent surface finish. Minimises costs associated with die repolishing.
- Excellent detergency. Removes metallic fines and particles from dies, eliminating defects associated with particulates. Improved surface finish, reducing scrap and rework costs.
- Relatively low viscosity, provides excellent cooling on high speed, multi stage operations, whilst minimising drag out, hence reducing product consumption.

Typical Characteristics

	Test Method	Unit	Value
Appearance	Visual	Visual	Hazy brown fluid
Viscosity @ 40°C	DIN 51562	mm ² /s	67
Density @ 15°C	DIN 51757	kg/m ³	1004
Flashpoint	ISO 2592	°C	> 170

Ester	Sulphur	Phosphorous	Chlorine	Other
✓	✓	✓	✓✓✓	✓

User Advice

Iloform PN 226 can be easily cleaned using mild alkaline or solvent cleaners.

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always.

For more details, please refer the product safety data sheet.

Castrol, Iloform PN, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material.

All products, services and information supplied are provided under our standard conditions of sale.

You should consult our local representative if you require any further information.

Deutsche BP AG – Industrial Lubricants & Services, Erkelenzer Str. 20, 41179 Mönchengladbach

Tel: +49 (0)2161 909-30 Fax: +49 (0)2161 909-481

www.castrol.com